EBG 194-UK



FR-A741

Frequency Inverter

With Power Regeneration

Conserves energy, cuts costs





Integrated power regeneration enhances energy efficiency



Much lower installation overheads, more effective system planning, simpler switchgear cabinet layout



High-end drive with a wealth of application functions



Lower TCO than conventional solutions

High-end drive performance



The new FR-A741 can save a lot of power in applications suitable for regenerative braking



Complex conveyor systems have potential for significant energy savings

Integrated power regeneration

The FR-A741 is the latest addition to the high-performance FR-A700 series. It sets new standards with an integrated power regeneration function that also improves braking performance. Featuring a large number of innovative technologies, this compact frequency inverter delivers exceptional performance and is ideal for hoist drives and high-powered machines with torque that can be used for regenerative braking. This includes a wide range of applications with vertical and horizontal movements such as conveyor systems, centrifugal separators, testing machines, winding machines and so on.

The new FR-A741 both reduces your initial investment outlay and keeps operating costs low. The integrated power regeneration function makes it possible to use smaller and much less expensive drive systems and enables simpler and more compact switchgear cabinet layouts. The advantages over conventional frequency inverter technology are very significant:

- 100 % braking energy infeed
- No braking resistor required
- Lower engineering overheads
- Minimizes braking heat generation
- Low installation overheads
- High energy efficiency
- Integrated AC reactor

High power saving potential

Cutting energy consumption and protecting the environment are now key issues in mechanical and plant engineering. Drive motors usually account for most of the power used and they also take up lots of space and require special cooling facilities. The FR-A741's regenerative braking system makes it much more efficient than conventional drive systems, giving it the potential for significant energy savings.

Feeding the energy generated by braking back into the power grid generates much less heat than a braking resistor. In addition to cutting power consumption this also reduces installation space requirements by eliminating the need for cooling hardware.

But that's not all – the energy fed back into the grid can also be used for other purposes, reducing operating costs still further.

Simpler installation

The integration of the frequency inverter and power regeneration system in a single unit reduces space requirements, making installation in the switchgear cabinet much simpler.



Integration of three functions in a single unit significantly reduces space requirements

The combination of the integrated AC reactor and no need for an external braking unit eliminate a large amount of additional wiring. These inverters need up to 60 % less main circuit wiring and occupy up to 40 % less space than conventional solutions, depending on the output capacity. The result is significantly less overall cable lengths and switchgear cabinet space requirements.

Economical even at low outputs

An efficient drive solution can usually pay for itself within a few months. An FR-A741 inverter with power regeneration can even achieve this for applications with lower power requirements and standard motors.


For example, in a shelf access system lifting drive application the hardware investment and energy costs of a conventional 22 kW inverter with a braking unit, braking resistor and AC reactor come to \in 12,839 per year.

In comparison, the FR-A741 inverter with power regeneration costs just € 8,840 per year, including the purchase price of the inverter itself.

This is a saving of 32 % in the first year alone, which is further compounded by additional high savings in power costs in the following years.

Ideal for hoisting applications

The frequency inverters of the FR-A741 series are innovative and intelligent drive systems that can easily be integrated in complex applications. They are particularly well suited for tasks involving frequent cyclical acceleration and deceleration and in all applications where braking resistors are normally used.



The FR-A741 is ideal for cranes and other hoisting and conveyor applications

Special crane programming functions are supported for easy integration in hoisting applications, including a special external brake control sequence, functions for load-based speed switching and four independent torque thresholds for all four quadrants.

Trouble-free mains operation

The FR-A741 has no special requirements as regards power supply perturbations – it is no more demanding in this respect than a standard frequency inverter.

Harmonic mains interference is efficiently suppressed by an integrated AC reactor. An additional harmonics suppression option is also available to further minimise network interference.

Proven high-end operation

The FR-A741 was developed on the basis of the reliable FR-A700 and has all the features you would expect from a high-end drive, including operating time monitoring, network support, long-life components, eco-friendliness and simple operation and maintenance.

Mitsubishi Electric frequency inverters are famous for their longevity. The FR-A741 is specified for a 10-year service life. Among other things, this is made possible by high-performance heat-resistant capacitors and cooling fans with sealed bearings.

The full output capacity of the inverter is available without restrictions up to an operating frequency of 14.5 kHz.

Conforms to international standards

Mitsubishi Electric frequency inverters meet all the requirements of the EU's 73/23/EEC Low Voltage Directive and 98/37/EC Machinery Directive. All inverters bear the CE mark and have UL, cUL and GOST certifications.















Specifications ///

| Overload rating | ND (normal duty) |
|---------------------|------------------|
| 60 seconds overload | 150 % |
| 3 seconds overload | 200 % |
| Ambient temperature | 50 °C |

| Model | Rated current [A]* | Motor capacity [kW] * | W x H x D (mm) |
|---------------|--------------------|--------------------------|-----------------|
| FR-A741-5.5k | 12 | 5.5 | 250 x 470 x 270 |
| FR-A741-7.5k | 17 | 7.5 | 250 x 470 x 270 |
| FR-A741-11k | 23 | 11 | 300 x 600 x 294 |
| FR-A741-15k | 31 | 15 | 300 x 600 x 294 |
| FR-A741-18.5k | 38 | 18.5 | 360 x 600 x 320 |
| FR-A741-22k | 44 | 22 | 390 x 600 x 320 |
| FR-A741-30k | 57 | 30 | 450 x 700 x 340 |
| FR-A741-37k | 71 | 37 | 470 x 700 x 368 |
| FR-A741-45k | 86 | 45 | 470 x 700 x 368 |
| FR-A741-55k | 110 | 55 | 600 x 900 x 405 |





| Operation | Data |
|-----------------------------|-----------------------------------|
| Power supply | 3-phase, 380-480 V (-15 %, +10 %) |
| Output frequency range | 0 – 400 Hz |
| Regenerative braking torque | 100 % continuous, 150 % for 60 s |
| Cooling | Fan |
| Protection rating | IP00 |
| Certifications | CE/UL/cUL/GOST |

| Environment | Data |
|-----------------------|----------------------------------|
| Ambient temperature | -10 °C − +50 °C (non-condensing) |
| Storage temperature | -20 °C − +65 °C |
| Relative humidity | Max. 90 % (non-condensing) |
| Installation altitude | Max. 1000 m above sea level |
| Vibration | Max. 0.6 G |
| Physical shock | 10 G |

| Available opti | ons | Designation | Description |
|--------------------------|-----------------------|-------------|--|
| Digital input | Digital input FR-A7AX | | Additional user-configurable inputs |
| Digital output | | FR-A7AY | Enables selectable frequency inverter output signals to be directed to open collector outputs. |
| Additional analog output | | rr-A/A1 | Enables output of additional analog signals as voltage or current values. |
| Relay output FR-A7AR | | FR-A7AR | Enables output of frequency inverter output signals to relay contacts. |
| Communications | Profibus/DP | FR-A7NP | Connect frequency inverter to a Profibus/DP network. |
| | DeviceNet | FR-A7ND | Connect frequency inverter to a DeviceNet network. |
| | CC-Link | FR-A7NC | Connect frequency inverter to a CC-Link network. |
| | LonWorks | FR-A7NL | Connect frequency inverter to a LonWorks network. |
| | CANopen | FR-A7NCA | Connect frequency inverter to a CANopen network. |
| | Ethernet | FR-A7N-ETH | Connect frequency inverter to an Ethernet network. |

EUROPEAN BRANCHES

MITSURISHI ELECTRIC EUROPER V C7ECH REPUBLIC Radlická 714/113a CZ-158 00 Praha 5 Phone: +420 (0)251 551 470 MITSUBISHI ELECTRIC EUROPE B.V. FRANCE 25. Boulevard des Bouvets F-92741 Nanterre Cedex Phone: +33 (0)1 / 55 68 55 68 MITSUBISHI ELECTRIC EUROPE B.V. Gothaer Straße 8 D-40880 Ratingen Phone: +49 (0)2102 / 486-0 MITSUBISHI ELECTRIC EUROPE B.V. GERMANY IRELAND siness Park, Bally IRL-Dublin 24 Phone: +353 (0)14198800 MITSUBISHI FI FCTRIC FUROPE B.V ITALY **I-20041 Agrate Brianza (MI)** Phone: +39 039 / 60 53 1 MITSUBISHI ELECTRIC EUROPE B.V. SPA
Carretera de Rubí 76-80
E-08190 Sant Cugat del Vallés (Barcelona)
Phone: 902 131121 / 1-34035653331 MITSUBISHI ELECTRIC EUROPE B.V.

GEVA AUSTRIA B:TECH A.S. AT-2500 Baden Phone: +43 (0)2252 / 85 55 20 CZ-58001 Havlíčkův Brod Phone: +420 (0)569 777 777 TEHNIKON BELARUS Oktyabrskaya 16/5, Off. 703-711 BY-220030 Minel Beijer Electronics A/S DENMARK BY-220030 Minsk Phone: +375 (0)17 / 210 46 26 **DK-4000 Roskilde** Phone: +45 (0)46/75 76 66 Koning & Hartman b.v. BI Woluwelaan 31 BE-1800 Vilvoorde Phone: +32 (0)2 / 257 02 40 BELGIUM Beijer Electronics Eesti OÜ ESTONIA **EE-11317 Tallinn** Phone: +372 (0)6 / 51 81 40 INEA BH d.o.o. BOSNIA AND HERZEG. Beijer Electronics OY **BA-71000 Sarajevo** Phone: +387 (0)33 / 921 164 FIN-01620 Vantaa e: +358 (0)207 / 463 500 GREECE AKHNATON BULGARIA 4 Andrej Ljapchev Blvd. Pb 21 **GR-18542 Piraeus** Phone: +30 211 / 1206 900 **BG-1756 Sofia** Phone: +359 (0)2 / 817 6004 MELTRADE Ltd. CROATIA HUNGARY Losinjska 4 a **HR-10000 Zagreb** Phone: +385 (0)1/36 940 - 01/-02/-03 HU-1107 Budapest Phone: +36 (0)1 / 431-9726 Kazpromautomatics Ltd. KAZAKHSTAN Mustafina Str. 7/2 AutoCont C.S. s.r.o. CZECH REPUBLIC Technologická 374/6 **CZ-708 00 Ostrava-Pustkovec** Phone: +420 595 691 150

C7ECH REPUBLIC Reijer Flectronics SIA LATVIA CONSYS LV-1035 Riga Phone: +371 (0)784 / 2280 Beijer Electronics UAB LITHUANIA Savanoriu Pr. 187 **LT-02300 Vilnius** Phone: +370 (0)5 / 232 3101 MOLDOVA Koning & Hartman b.v. NETHERLANDS Haarlerbergweg 21-23 NL-1101 CH Amsterdam Phone: +31 (0)20 / 587 76 00 Beijer Electronics AS Postboks 487 NORWAY **NO-3002 Drammen** Phone: +47 (0)32 / 24 30 00 MPL Technology Sp. z o.o. POLAND UI. Krakowska 50 PL-32-083 Balice Phone: +48 (0)12 / 630 47 00 Sirius Trading & Services ROMANIA
Aleea Lacul Morii Nr. 3 RO-060841 Bucuresti, Sector 6

Promyshlennaya st. 42 **RU-198099 St. Petersburg** Phone: +7 812 / 325 36 53 ELECTROTECHNICAL SYSTEMS RUSSIA Derbenevskaya st. 11A, Office 69 **RU-115114 Moscow** Phone: +7 495 / 744 55 54 Phone: -7 495 / 744 55 54

ELEKTROSTILY

Rubzowskaja nab. 4-3, No. 8

RU-105082 Moscow

Phone: -7 495 / 545 3419

RPS-AUTOMATIKA

RUS

RU-34007 Rostov on Don

Phone: -7 4863 / 22 63 72

STC Drive Technique
1-st Magistralny tupik, 10, lid. 1

RU-123290 Moscow **RU-123290 Moscow** Phone: +7 495 / 786 21 00 Craft Con. & Engineering d.o.o. SERBIA Bulevar Svetog Cara Konstantina 80-86 SER-18106 Nis Phone: +381 (0)18 / 292-24-4/5 SERBIA INEA SR d.o.o. SER-113000 Smederevo Phone: +381 (0)26 / 617 163

RUSSIA AutoCont Control s.r.o. SLOVAKIA SHERF Motion Techn, Ltd. ISRAEL SK-02601 Dolny Kubin Phone: +421 (0)43 / 5868210 CS MTrade Slovensko, s.r.o. SLOVAKIA **SK-92101 Piestany** Phone: +421 (0)33 / 7742 760 INEA d.o.o. SLOVENIA Stegne 11 SI-1000 Ljubljana Phone: +386 (0)1 / 513 8100 Beijer Electronics AB Box 426 SE-20124 Malmö Phone: +46 (0)40 / 35 86 00 Econotec AG Hinterdorfstr. 12 SWITZERLAND **CH-8309 Nürensdorf** Phone: +41 (0)44 / 838 48 11 GFS TURKEY
Darülaceze Cad. No. 43 KAT. 2
TR-34384 Okmeydanı-Istanbul
Phone: +90 (0)212/320 1640
CSC Automation 1+3 CSC Automation Ltd. UKR 4-B, M. Raskovoyi St. UA-02660 Kiev Phone: +380 (0)44 / 494 33 55

IL-58851 Holon Phone: +972 (0)3 / 559 54 62 SOUTH AFRICA **ZA-1600 Isando** Phone: + 27 (0)11 / 928 2000



UK-Hatfield, Herts. AL10 8XB Phone: +44 (0)1707 / 27 61 00