



Kinco New Products for MT4000 Widescreen Series >

Kinco
Create Value for Global Customer



Product Features:

High performance: With 400-800MHz CPU, higher efficiency.
Backlight: LED, more energy conservation.
Communication: Serial ports, USB port, Ethernet ports.
Wide screen: 16:9 wide screen.

Model of New Products:



MT4210T / MT4220TE



MT4414T / MT4414TE



MT4512T / MT4512TE

Model	MT4210T	MT4220TE	MT4414T	MT4414TE	MT4512T	MT4512TE
Display	4.3" TFT		7" TFT		10.1" TFT	
Color	65536 Colors		65536 Colors		65536 Colors	
Resolution	480×272		800×480		800×480	
Backlight	LED		LED		LED	
CPU	400MHz RISC	800MHz RISC	400MHz RISC	800MHz RISC	400MHz RISC	800MHz RISC
Memory	128M FLASH+64M SDRAM		128M FLASH+64M SDRAM		128M FLASH+64M SDRAM	
RTC&Recipe memory	RTC + 512KB		RTC + 512KB		RTC + 512KB	
Expandable memory	None	1 USB Host + 1 SD Card	None	1 USB Host	None	1 USB Host
Serial port	COM0: RS232/RS485-2/4; COM2: RS232					
Printer port	Serial port	USB/Serial port	Serial port	USB/Serial port	Serial port	USB/Serial port
Ethernet	None	Support	None	Support	None	Support
Program download	USB/Serial port	USB/Ethernet/ Serial port	USB/Serial port	USB/Ethernet/ Serial port	USB/Serial port	USB/Ethernet/ Serial port
Dimensions	154×89×59.8mm		204×150×37 mm		310×230×55 mm	
Cutout size	145×81mm		192×138 mm		298×218 mm	
Rated power	3.5W		4W		8W	
Input range	12 ~ 28VDC		12 ~ 28VDC		12 ~ 28VDC	
Operation temperature	-20 ~ 55°C		0 ~ 45°C		0 ~ 45°C	
Storage temperature	-25 ~ 60°C		-10 ~ 60°C		-10 ~ 60°C	
Operation humidity	10 ~ 90%RH (non-condensing)					
Shell material	ABS Plastic					
Degree of protection	IP65(4208-93)(front panel)					