MITSUBISHI

GOT1000 STAND

User's Manual

GT15-90STAND GT15-80STAND GT15-70STAND GT05-50STAND

Thank you for purchasing the GOT1000 Series.

Prior to use, please read both this manual and detailed manual thoroughly to fully understand the product.

MODEL	GT15-STAND-U	
MODEL CODE	1D7M00	
IB(NA)-0800294-D(0603)MEE		



●SAFETY PRECAUTIONS●

(Always read these precautions before using this equipment.)

Before using this product, please read this manual and the relevant manuals introduced in this manual carefully and pay full attention to safety to handle the product correctly.

The precautions given in this manual are concerned with this prod-

In this manual, the safety precautions are ranked as "DANGER" and "CAUTION".

Indicates that incorrect handling may cause ♦ DANGER hazardous conditions, resulting in death or

Indicates that incorrect handling may cause ⚠ CAUTION hazardous conditions, resulting in medium or slight personal injury or physical damage.

Note that the $\stackrel{\textstyle \wedge}{\underline{\ \ }}$ CAUTION level may lead to a serious accident according to the circumstances.

Always follow the precautions of both levels because they are impor-

tant to personal safety. save this manual to make it accessible when required and

always forward it to the end user.

[INSTALLATION PRECAUTIONS]

DANGER

Make sure to externally shut off the all phases of the system power supply before mounting/removing the GOT onto/from the stand. Failure to do so may cause the unit to fail or malfunction

⚠ CAUTION

- Use this stand in an environment which satisfies the general specifications described in the GT15 User's Manual. Using in an environment other than that satisfies the general specifications may cause an electric shock, a fire, or damage o deterioration to the GOT.
- Be careful not to get your finger caught when removing the angle adjusting screws from the stand and adjusting the mounting angle
- When mounting the GOT onto the stand, fix it with the mounting fixtures securely and tighten the screws in the specified torque Loose tightening may cause the GOT to drop off from the stand
- Make sure that mounting angle is 45, 55, 65 or 75 degrees, when adjusting the mounting angel with the GOT mounted on the stand.

If mounting angle is set to other than above, the GOT bottom may interfere with the stand bottom, resulting in the GOT damage.

[DISPOSAL PRECAUTIONS]

⚠ CAUTION

Dispose of this product as industrial waste.

The following shows manuals relevant to this product.

Detailed Manual

Manual name		Manual number (Type code)	
GT15 User's Manual	(Option)	SH-080528ENG (1D7M23)	

Relevant Manuals

For relevant manuals, refer to the PDF manual stored within the drawing software used.


© 2004 MITSUBISHI ELECTRIC CORPORATION

1. Overview

This User's Manual describes the GOT1000 series stand (hereafter abbreviated to the stand). Refer to the GT15 User's Manual for the applicable GOT.


Product name	Model name	Description		
Stand	GT15-90STAND	For 15" GOT		
	GT15-80STAND	For 12.1" GOT		
	GT15-70STAND	For 8.4", 10.4" GOT		
	GT05-50STAND	For 8.4", 10.4" GOT		

The stand is useful for debugging the GOT screen data, as it can set the GOT at a proper angle on a table.



2. How to Use Stand

(1) GT15-90STAND, GT15-80STAND, GT15-70STAND 1) Adjust the mounting angle with the angle adjusting screw.



2) Put the GOT into the Stand from the front and fix it using For the GOT mounting method, refer to the GT15 User's

3) After the installation, perform wiring, etc


(2) GT05-50STAND

 Determine the angle for installing the GOT.
 Slide the angle adjustment fitting as shown below to determine the angle.


The angle can be adjusted to 75°, 65°, 55° or 45°. When installing multiple units to the GOT, use the stand with 75 or 65 degrees for securing lead-in allowances for cables at the bottom of the GOT.



2) Once the angle is determined, insert the angle adjustment fitting's fixing hook into the hook insertion section on the bottom of the stand



3) Securely tighten the fixing screw



4) Insert the GOT from the front of Stand and install it to Refer to the GT15 User's Manual for details on installing

5) After the installation, perform wiring, etc.

Warranty

Mitsubishi will not be held liable for damage caused by factors found not to be the cause of Mitsubishi; machine damage or lost profits caused by faults in the Mitsubishi products; damage, secondary damage, accident compensation caused by special factors unpredictable by Mitsubishi; damages to products other than Mitsubishi products; and to other duties.

⚠ For safe use

- This product has been manufactured as a general-purpose part for general industries, and has not been designed or manufactured to be incorporated in a device or system used in purposes related to
- Before using the product for special purposes such as nuclear power, electric power, aerospace, medicine or passenger movement vehicles, consult with Mitsubishi.

 This product has been manufactured under strict quality control.
- However, when installing the product where major accidents or losses could occur if the product fails, install appropriate backup or failsafe functions in the system.

Country/Region Sales office/Tel U.S.A Mitsubishi Electri Brazil

Germany U.K Italy

Indonesia

n Sales office/Tel
Mitsubishi Electric Automation Inc.
500 Corporate Woods Parkway Vernon Hills, IL 60061
Tel: +1-847-478-2100
MELCO-TEC Rep. Come Assessoria Tecnica Ltda.
Rua Correia Dias, 184, Edificio Paraiso Trade Center-8 andar
Paraiso, Sao Paulo, SP Brazil
Tel: +55-11-5908-8331
Mitsubishi Electric Europe B.V. German Branch
Gothaer Strasse B 0-40680 Ratingen, GERMANY
Tel: +49-2102-486-0
Mitsubishi Electric Europe B.V. UK Branch
Travellers Lane, Hatfield, Herts, Al-10 8XB, UK
Tel: +44-1707-276100
Mitsubishi Electric Europe B.V. Italian Branch
Centro Dir. Colleoni, Pal. Perseo-Ingr.2
Via Paracelso 12, 20041 Agrate B, Milano, Italy
Tel: +39-039-605344
Mitsubishi Electric Europe B.V. Spanish Branch
Carretera de Rubi 76-80
Mitsubishi Electric Europe B.V. Spanish Branch
Carretera de Rubi 76-80
Mitsubishi Electric Europe B.V. Spanish Branch
Carretera de Rubi 76-80
Mitsubishi Electric Europe B.V. Spanish Branch
Carretera de Rubi 76-80
Mitsubishi 2015-810
Mitsubishi Electric Europe B.V. Spanish Branch

08190 - Sant Cugat del Valles, Barcelona, Spain Tel: +34-93-565-3131

rei: +34-93-565-3131
Mitsubishi Electric Europe B.V. French Branch
25 Boulevard des Bouvets, F-92741 Nanterre Cedex, France
TEL: +33-1-5568-5568
Circuit Breaker Industries LTD.
Tripswitch Drive, Elandsfontein Gauteng, South Africa
Tel: +27-11-928-2000 France South Africa

Hong Kong

China

Ryoden Automation Ltd.
10th Floor, Manulife Tower, 169 Electric
Road, North Point, HongKong
Tel: +852-2887-8870
Ryoden Automation Shanghai Ltd.
3F Blocks Building Automation
Instrumentation Plaza 103 Cao Bao Rd. Shanghai 200233 China
Tel: +86-21-612-0-0088
Setsuyo Enterprise Co., Ltd.
6F., No. 105 Wu-Kung 3rd.RD, Wu-Ku Hsiang,
Taipel Hsine, Tailwan
Tel: +866-2-2299-2499
HAN NEUNG TECHNO CO.,LTD.
1F Dong Seo Game Channel Bidg.,660-11, Deungchon-dong
Kangsec-Ku, Seoul, Korea
Tel: +82-2-3660-9552
Tel: +82-2-3660-9552
Mitsubishi Electric Asia Pte, Ltd. Korea

Mitsubishi Electric Asia Pte, Ltd. 307 Alexandra Road #05-01/02.

Singapore

307 Alexandra Road #05-01/02, Mitsubish IEctric Building Singapore 159943 Tel. : +65-8473-2308 Tel. : +662-852-852 Tel. : +662-862-852

India


Tel:+62-21-663-0833 Messung Systems Put,Ltd. Electronic Sadan No:111 Unit No15, M.I.D.C BHOSARI, PUNE-411026, India Tel:+91-20-712-2807 Mitsubishi Electric Australia Pty. Ltd. 348 Victoria Road, PostalBag, No 2, Rydalmere, N.S.W 2116, Australia Tel:+61-2-9684-7777

★MITSUBISHI ELECTRIC CORPORATION

HEAD OFFICE : TOKYO BUILDING, 2-7-3 MARUNOUCHI, CHIYODA-KU, TOKYO 100-8310, JAPAN NAGOYA WORKS : 1-14, YADA-MINAMI 5-CHOME, HIGASHI-KU, NAGOYA, JAPAN

When exported from Japan, this manual does not require application to the Ministry of Economy, Trade and Industry for service transaction permission.

3. External Dimensions



Model name	Type of GOT mounted	Α	В	C*	D	Е	F
GT15- 90STAND	When 15" GOT is mounted	444 (17.5)	200 (7.9)	364 (14.3)	4 (0.16)	65 (2.56)	8.7 (0.34)
GT15- 80STAND	When 12.1" GOT is mounted	334 (13.1)	200 (7.9)	345 (13.6)	4 (0.16)	63 (2.48)	8.7 (0.34)
GT15- 70STAND	When 10.4" GOT is mounted	314 (12.4)	300 (11.8)	327 (12.9)	4 (0.16)	63 (2.48)	8.7 (0.34)
	When 8.4" GOT is mounted	314 (12.4)	335 (13.2)	294 (11.6)	4 (0.16)	63 (2.48)	8.7 (0.34)
GT05- 50STAND	When 5.7" GOT is mounted	210 (0.83)	260 (10.24)	254 (10)	4 (0.16)	40 (1.57)	5 (0.2)
50STAND		(0.83)	(10.24)	(10)	, ,	(1.57)	` '

Unit: mm (inch) * Dimensions for mounting angle of 75 degrees

Model name	Weight
GT15-90STAND	1.7kg
GT15-80STAND	1.9kg
GT15-70STAND	1.5kg
GT05-50STAND	1.1kg